Color Laser Printer/ Color Laser MFP

RICOH SP C252DN/ SP C252SF



SP C252DN SP C252SF



Discover the freedom of productivity

As business moves faster, we're all using mobile devices to keep pace — changing how we work, and in many cases, where we work. Ricoh continues to do its part, with new innovations offering more freedom and agility, so you can perform more everyday tasks in less time. Looking for color wireless printing? Choose the RICOH* SP C252DN and produce professional-quality documents from anywhere. Need to share documents quickly with coworkers and customers? Add copying, scanning, faxing and more with the Ricoh SP C252SF. Tight on space? These desktop devices are small enough to fit in cramped spaces, making them convenient for smaller offices. You can even include them as part of a Ricoh Managed Document Services (MDS) strategy and measure how much time and money they can save for your organization.

Work quickly, from anywhere

Complete more office tasks in less time. Black-and-white and color pages print at 21 pages per minute, and first prints are available in only 14 seconds, so you can complete even large print jobs quickly. Best of all, you can do it from anywhere. The Ricoh SP C252DN/SP C252SF comes standard with secure IEEE 802.11b/g/n Wireless LAN connectivity, so you can put it on the desktop, in a cabinet or under the counter with ease, and without an unsightly tangle of cords. Download the Ricoh Smart Device Print&Scan app and print directly from your personal mobile device. Or, take your work with you. Simply connect your digital camera or SD card into the strategically placed USB port on the front of the device to print documents and images without a computer.

Save space, save time

From the corner office to the corner store, the Ricoh SP C252DN/SP C252SF fits almost any workspace. Choose tasks, check settings and move to the next job in moments using the intuitive LCD display on the control panel. You can even choose frequently used tasks with one-touch control for incredible speed and convenience. Changing cartridges is just as easy. The all-in-one print cartridges can be replaced by anyone, without any training or mess.

Produce quality color at an affordable price

Color can make everyday business documents more dynamic and compelling. The Ricoh SP C252DN/SP C252SF makes color more affordable, too. In Economy Color Mode, you can print text at full density, but use less toner for images to significantly reduce cost-per-page. When you need sharper lines, more precise text and vibrant colors, the device offers true 600 x 600 dpi resolution. Need to print a professional-looking document without outsourcing? Print at even higher resolutions up to 2,400 x 600 dpi for business presentations that require eye-catching, higher quality graphics.







Versatile, fully featured performance for small offices

Perform every task with ease

Whether you're printing documents, or sharing them with others, the Ricoh SP C252SF lets you have it all in a single, compact device. Share fullcolor documents using a wide range of scan-to options or a USB Flash Drive. Use the 35-Sheet Automatic Document Feeder to manage multiple-page documents quickly. Store up to 200 speed dial entries and send secure faxes to frequent recipients quickly using one-touch control keys. You can even copy two-sided documents, such as drivers' licenses, insurance cards and more, onto a single side of a sheet of paper using the ID Card Copy feature.

Add value in and out of the office

Looking for a powerful, versatile device that's as friendly to the environment as it is to your budget? Choose the Ricoh SP C252DN/ SP C252SF for low hardware costs along with superior cost per page savings. Print on both sides of paper with duplex printing and save on paper costs. Use less energy while taking advantage of this ENERGY STAR[™] certified device's low typical electricity consumption (TEC) value. Plus, take advantage of our consumables recycling programs to promote a resource recirculating society.





Protect sensitive information

Information is the most important asset in your office. Protect it with advanced user authentication controls. Store every document securely until an authorized user enters the correct PIN from the Ricoh SP C252DN/SP C252SF control panel. No more sensitive information is left unattended in the output tray for any passersby to read. Worried about supply levels or need to check network settings? Use Web Image Monitor to resolve maintenance issues — and even prevent them — from any location.

Incredible ease of use and convenience

Simplify your workload with unmatched convenience that builds on Ricoh's legacy of affordable, timesaving innovations for the workplace. Complete a wide range of tasks with a single touch using the intuitive control panel with LCD screen. Check supply status and make corrections directly at the device. Not in the office? Use Ricoh's Web Image Monitor to perform many of the same tasks remotely. You can also change the top-loading, all-in-one print cartridges in moments without help and without a mess.





Ricoh SP C252DN/SP C252SF

SYSTEM SPECIFICATIONS

General Specifications SP C252DN Part # 407521

CD COEOCE	Part # 407521		
SP C252SF Configuration	Part # 407525 Desktop		
Imaging Process	Laser beam scanning, color		
initiging recess	electrophotographic printing with		
	monocomponent toner development		
	4-drum tandem method		
Scanning Element	Flatbed scanner with full color contact image		
	sensor (CIS)		
Print Resolution	600 x 600 dpi (Default) (Speed Mode)		
	1200 x 600 dpi equivalent (Standard Mode)		
Print Speed (Letter)	2400 x 600 dpi equivalent (Fine Mode) SP C252DN: 21 ppm B&W and Full-Color;		
Fint speed (Letter)	12 ppm duplex		
Print/Copy Speed (Letter)	SP C252SF: 21 ppm/cpm B&W and Full-Color;		
init copy speed (Letter)	12 ppm/cpm duplex		
First Print Speed	14 seconds or less		
Warm-Up Time	30 seconds or less (from Energy Saver Mode)		
Operating Systems	Windows XP/Vista/7/8/Server 2003/2003R2/		
1 3 9	2008/2008R2/2012 (32 bit/64 bit) and later;		
	Mac OS X 10.6 and later; Citrix MetaFrame		
Software Utilities	Web Image Monitor, Presto! PageManager		
	version 9.33 (SP C252SF only), @Remote		
	Office Appliance, @Remote Enterprise Pro		
	On-Site, @Remote Enterprise Pro Connector		
	Option, Device Manager NX Lite, Printer		
	Driver Packager NX, Web Based Driver		
Standard Paper Capacity	Installer (WBDI) 250-sheet Paper Tray + 1-sheet Bypass Tray		
Optional Paper Capacity	500-sheet Paper Feed Unit		
Maximum Input	751 sheets		
Output Capacity	150 sheets (face down)		
Automatic Duplex	Standard		
Paper Sizes	Standard Tray and Bypass Tray: Letter (8.5"		
	x 11"), Legal (8.5" x 14"), EXEC (10.5" x		
	7.25"), Half Letter (5.5" x 8.5"), A4 (8.3" x		
	11.7"), A5 (5.8" x 8.3"), A6 (4.1" x 5.8"),		
	B5 JIS (7.2" x 10.1"), B6 JIS (5.0" x 7.2"),		
	F (8" x 13"), Foolscap (8.5" x 13"), Folio		
	F (8" x 13"), Foolscap (8.5" x 13"), Folio (8.25" x 13"), 16 Kai (7.6" x 10.5")		
	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL		
	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54"		
	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x		
	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0")		
	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"),		
Paper Weight	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7")		
Paper Weight	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7") Standard Tray and Bypass Tray: 16 – 42 lb.		
Paper Weight	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7") Standard Tray and Bypas Tray: 16 – 42 lb. Bond/83 lb. Index (60 – 160 g/m ²)		
Paper Weight	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7") Standard Tray and Bypass Tray: 16 – 42 lb. Bond/83 lb. Index (60 – 160 g/m") Duplex: 16 – 24 lb. Bond (60 – 90 g/m")		
Paper Weight	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7") Standard Tray and Bypass Tray: 16 – 42 lb. Bond/83 lb. Index (60 – 160 g/m") Duplex: 16 – 24 lb. Bond (60 – 90 g/m") Optional Paper Feed Unit: 16 – 28 lb. Bond		
	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7") Standard Tray and Bypass Tray: 16 – 42 lb. Bond/83 lb. Index (60 – 160 g/m') Duplex: 16 – 24 lb. Bond (60 – 90 g/m') Optional Paper Feed Unit: 16 – 28 lb. Bond (60 – 105 g/m')		
Paper Weight Acceptable Paper Types	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7") Standard Tray and Bypass Tray: 16 – 42 lb. Bond/83 lb. Index (60 – 160 g/m") Duplex: 16 – 24 lb. Bond (60 – 90 g/m") Optional Paper Feed Unit: 16 – 28 lb. Bond (60 – 105 g/m") Standard Tray and Bypass Tray: Plain Paper,		
	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7") Standard Tray and Bypass Tray: 16 – 42 lb. Bond/83 lb. Index (60 – 160 g/m') Duplex: 16 – 24 lb. Bond (60 – 90 g/m') Optional Paper Feed Unit: 16 – 28 lb. Bond (60 – 105 g/m') Standard Tray and Bypass Tray: Plain Paper, Middle Thick, Recycle Paper, Envelopes, Thick		
	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7") Standard Tray and Bypass Tray: 16 – 42 lb. Bond/83 lb. Index (60 – 160 g/m") Duplex: 16 – 24 lb. Bond (60 – 90 g/m") Optional Paper Feed Unit: 16 – 28 lb. Bond (60 – 105 g/m") Standard Tray and Bypass Tray: Plain Paper, Middle Thick, Recycle Paper, Envelopes, Thick Paper, Labels, Thin Paper, Color Paper, Pre-		
	$ \begin{array}{l} (8.25" \times 13"), 16 \ Kai (7.6" \times 10.5") \\ \mbox{Envelopes: Com10, Monarch, C5, C6, DL \\ \mbox{Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") \\ \mbox{Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7') \\ \mbox{Standard Tray and Bypass Tray: 16 - 42 lb. \\ \mbox{Bond/83 lb. Index (60 - 160 g/m') \\ \mbox{Optional Paper Feed Unit: 16 - 28 lb. Bond \\ \mbox{(60 - 160 g/m') } \\ \mbox{Optional Paper Feed Unit: 16 - 28 lb. Bond \\ \mbox{(60 - 105 g/m') } \\ \mbox{Standard Tray and Bypass Tray: Plain Paper, \\ \mbox{Midle Thick, Recycle Paper, Envelopes, Thick \\ \mbox{Paper, Labels, Thin Paper, Color Paper, Pre-punched Paper, Letterhead, Bond Paper, Card \\ \end{array} } $		
	$ \begin{array}{l} (8.25" \times 13"), 16 \ Kai (7.6" \times 10.5") \\ \mbox{Envelopes: Com10, Monarch, C5, C6, DL \\ \mbox{Custom size: Min. 90 mm x 148 mm (3.54" x 14.0") \\ \mbox{Dystar} (3.53" , Max. 216 mm x 356 mm (8.5" x 11.4.0") \\ \mbox{Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7") \\ \mbox{Standard Tray and Bypass Tray: 16 - 42 lb. \\ \mbox{Bond/83 lb. Index (60 - 160 g/m") \\ \mbox{Optional Paper Feed Unit: 16 - 28 lb. Bond \\ \mbox{(60 - 105 g/m") } \\ Optional Paper, Envelopes, Thick \\ \mbox{Paper, Latterhead, Bond Paper, Card \\ \mbox{Standard Tray and Bypass Tray: Plain Paper, Card \\ \mbox{Standard Tray and Bypass Tray Bandard \\ \mbox{St$		
	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com 10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7") Standard Tray and Bypass Tray: 16 – 42 lb. Bond/83 lb. Index (60 – 160 g/m') Duplex: 16 – 24 lb. Bond (60 – 90 g/m') Optional Paper Feed Unit: 16 – 28 lb. Bond (60 – 105 g/m') Standard Tray and Bypass Tray: Plain Paper, Middle Thick, Recycle Paper, Envelopes, Thick Paper, Labels, Thin Paper, Color Paper, Pre- punched Paper, Letterhead, Bond Paper, Card Stock and Preprinted Paper (Std. Tray only) Optional Paper Feed Unit: Plain Paper,		
	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7") Standard Tray and Bypass Tray: 16 – 42 lb. Bond/83 lb. Index (60 – 160 g/m') Duplex: 16 – 24 lb. Bond (60 – 90 g/m') Optional Paper Feed Unit: 16 – 28 lb. Bond (60 – 105 g/m') Standard Tray and Bypass Tray: Plain Paper, Middle Thick, Recycle Paper, Storkelopes, Thick Paper, Labels, Thin Paper, Color Paper, Pre- punched Paper, Letterhead, Bond Paper, Card Stock and Preprinted Paper (Std. Tray only) Optional Paper Feed Unit: Plain Paper, Middle Thick, Recycle Paper, Thick Paper,		
	(8.25° x 13°), 16 Kai (7.6° x 10.5°) Envelopes: Com 10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54° x 5.83°), Max. 216 mm x 356 mm (8.5° x 14.0°) Optional Paper Feed Unit: Letter (8.5° x 11°), A4 (8.3° x 11.7°) Standard Tray and Bypass Tray: 16 – 42 lb. Bond/83 lb. Index (60 – 160 g/m') Duplex: 16 – 24 lb. Bond (60 – 90 g/m') Optional Paper Feed Unit: 16 – 28 lb. Bond (60 – 105 g/m') Standard Tray and Bypass Tray: Plain Paper, Middle Thick, Recycle Paper, Envelopes, Thick Paper, Labels, Thin Paper, Color Paper, Pre- punched Paper Letterhead, Bond Paper, Card Stock and Preprinted Paper (Std. Tray only) Optional Paper Feed Unit: Plain Paper, Middle Thick, Recycle Paper, Thick Paper, Middle Thick, Recycle Paper, Thick Paper, Thin Paper, Color Paper, Preprinted Paper,		
Acceptable Paper Types	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7") Standard Tray and Bypass Tray: 16 – 42 lb. Bond/83 lb. Index (60 – 160 g/m ³) Duplex: 16 – 24 lb. Bond (60 – 90 g/m ³) Optional Paper Feed Unit: 16 – 28 lb. Bond (60 – 105 g/m ³) Standard Tray and Bypass Tray: Plain Paper, Middle Thick, Recycle Paper, Envelopes, Thick Paper, Labels, Thin Paper, Color Paper, Pre- punched Paper, Letterhead, Bond Paper, Card Stock and Preprinted Paper (Std. Tray only) Optional Paper Feed Unit: Plain Paper, Middle Thick, Recycle Paper, Thick Paper, Thin Paper, Color Paper, Preprinted Paper, Prepunched Paper and Letterhead		
	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7') Standard Tray and Bypass Tray: 16 – 42 lb. Bond/83 lb. Index (60 – 160 g/m') Duplex: 16 – 24 lb. Bond (60 – 90 g/m') Optional Paper Feed Unit: 16 – 28 lb. Bond (60 – 105 g/m') Standard Tray and Bypass Tray: Plain Paper, Middle Thick, Recycle Paper, Envelopes, Thick Paper, Labels, Thin Paper, Color Paper, Pre- punched Paper, Letterhead, Bond Paper, Card Stock and Preprinted Paper (Std. Tray only) Optional Paper Feed Unit: Plain Paper, Middle Thick, Recycle Paper, Thick Paper, Thin Paper, Color Paper, Preprinted Paper, Prepunched Paper, Thick Paper, Thin Paper, Color Paper, Thick Paper, Thick Paper, Thin Paper, Color Paper, Thick Paper, Thick Paper, Thin Paper, Color Paper, Prepinted Paper, Paper, Pinter Paper, Paper, Paper, Paper, Paper, Paper, Paper, Pinter Paper, Paper, Paper, Paper, Paper, Paper, Pinter Paper, Paper, Paper, Paper, Paper, Paper, Pinter Paper, Paper, Paper, Paper, Pinter Paper, Paper, Paper, Paper, Paper		
Acceptable Paper Types	(8.25 " x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com 10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7") Standard Tray and Bypass Tray: 16 – 42 lb. Bond/83 lb. Index (60 – 160 g/m ³) Duplex: 16 – 24 lb. Bond (60 – 90 g/m ³) Optional Paper Feed Unit: 16 – 28 lb. Bond (60 – 105 g/m ³) Standard Tray and Bypass Tray: Plain Paper, Middle Thick, Recycle Paper, Envelopes, Thick Paper, Labels, Thin Paper, Color Paper, Pre- punched Paper Letterhead, Bond Paper, Card Stock and Preprinted Paper (Std. Tray only) Optional Paper Feed Unit: Plain Paper, Middle Thick, Recycle Paper, Thick Paper, Color Paper, Preprinted Paper, Color Paper, Preprinted Paper, Prepunched Paper and Letterhead SP C252DN: 15.7" x 17.7" x 12.6" (400 x 450 x 320 mm)		
Acceptable Paper Types	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7") Standard Tray and Bypass Tray: 16 – 42 lb. Bond/83 lb. Index (60 – 160 g/m') Duplex: 16 – 24 lb. Bond (60 – 90 g/m') Optional Paper Feed Unit: 16 – 28 lb. Bond (60 – 105 g/m') Standard Tray and Bypass Tray: Plain Paper, Middle Thick, Recycle Paper, Envelopes, Thick Paper, Labels, Thin Paper, Color Paper, Pre- punched Paper, Letterhead, Bond Paper, Card Stock and Preprinted Paper, Cist. Tray only) Optional Paper Feed Unit: Plain Paper, Middle Thick, Recycle Paper, Thick Paper, Middle Thick, Recycle Paper, Alter Middle Thick, Middle Thick, Recycle Paper, Middle Thick, Middle Thick, Recycle		
Acceptable Paper Types	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7') Standard Tray and Bypass Tray: 16 – 42 lb. Bond/83 lb. Index (60 – 160 g/m') Duplex: 16 – 24 lb. Bond (60 – 90 g/m') Optional Paper Feed Unit: 16 – 28 lb. Bond (60 – 105 g/m') Standard Tray and Bypass Tray: Plain Paper, Middle Thick, Recycle Paper, Envelopes, Thick Paper, Labels, Thin Paper, Color Paper, Pre- punched Paper, Letterhead, Bond Paper, Card Stock and Preprinted Paper (Std. Tray only) Optional Paper Feed Unit: Plain Paper, Middle Thick, Recycle Paper, Thick Paper, Thin Paper, Color Paper, Preprinted Paper, Pre- punched Paper and Letterhead SP C252DN: 15.7" x 17.7" x 12.6" (400 x 450 x 320 mm) SP C252SF: 16.5" x 19.4" x 18.1" (420 x 433 x 460 mm)		
Acceptable Paper Types	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com 10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7") Standard Tray and Bypass Tray: 16 – 42 lb. Bond'83 lb. Index (60 – 160 g/m') Duplex: 16 – 24 lb. Bond (60 – 90 g/m') Optional Paper Feed Unit: 16 – 28 lb. Bond (60 – 105 g/m') Standard Tray and Bypass Tray: Plain Paper, Middle Thick, Recycle Paper, Envelopes, Thick Paper, Labels, Thin Paper, Color Paper, Pre- punched Paper Letterhead, Bond Paper, Card Stock and Preprinted Paper (Std. Tray only) Optional Paper Feed Unit: Plain Paper, Middle Thick, Recycle Paper, Thick Paper, Prepunched Paper and Letterhead SP C252DN: 15.7" x 17.7" x 12.6" (400 x 450 x 320 mm) SP C252DN: 52.5 lb. (23.8 kg) (including		
Acceptable Paper Types	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7') Standard Tray and Bypass Tray: 16 – 42 lb. Bond/83 lb. Index (60 – 160 g/m') Duplex: 16 – 24 lb. Bond (60 – 90 g/m') Optional Paper Feed Unit: 16 – 28 lb. Bond (60 – 105 g/m') Standard Tray and Bypass Tray: Plain Paper, Middle Thick, Recycle Paper, Envelopes, Thick Paper, Labels, Thin Paper, Color Paper, Pre- punched Paper, Letterhead, Bond Paper, Card Stock and Preprinted Paper (Std. Tray only) Optional Paper Feed Unit: Plain Paper, Middle Thick, Recycle Paper, Thick Paper, Thin Paper, Color Paper, Preprinted Paper, Pre- punched Paper and Letterhead SP C252DN: 15.7" x 17.7" x 12.6" (400 x 450 x 320 mm) SP C252SF: 16.5" x 19.4" x 18.1" (420 x 433 x 460 mm)		
Acceptable Paper Types	(8.25" x 13"), 16 Kai (7.6" x 10.5") Envelopes: Com10, Monarch, C5, C6, DL Custom size: Min. 90 mm x 148 mm (3.54" x 5.83"), Max. 216 mm x 356 mm (8.5" x 14.0") Optional Paper Feed Unit: Letter (8.5" x 11"), A4 (8.3" x 11.7") Standard Tray and Bypass Tray: 16 – 42 lb. Bond/83 lb. Index (60 – 160 g/m') Duplex: 16 – 24 lb. Bond (60 – 90 g/m') Optional Paper Feed Unit: 16 – 28 lb. Bond (60 – 105 g/m') Standard Tray and Bypass Tray: Plain Paper, Middle Thick, Recycle Paper, Envelopes, Thick Paper, Labels, Thin Paper, Color Paper, Pre- punched Paper, Letterhead, Bond Paper, Card Stock and Preprinted Paper (Std. Tray only) Optional Paper Feed Unit: Plain Paper, Middle Thick, Recycle Paper, Thick Paper, Middle Thick, Recycle Paper, Thick Paper, Middle Thick, Recycle Paper, Thick Paper, Stock and Preprinted Paper, Clor Paper, Pre- punched Paper and Letterhead SP C252DN: 15.7" x 17.7" x 12.6" (400 x 450 x 320 mm) SP C252EN: 16.5" x 19.4" x 18.1" (420 x 493 x 460 mm) SP C252DN: 52.5 lb. (23.8 kg) (including consumables)		

Power Requirements Max. Power Consumption Energy Saver Mode	120V, 60Hz 1,300W or less SP C252DN: 2.4W SP C252SF: 2.4W	Facsimile Specif Circuit Compatibility Resolution
TEC	SP C252DN: 1.37 kWh/week SP C252SF: 1.48 kWh/week	Compression Method
Safety Regulations	UL60950-1 2nd Edition; CAN/CSA C22.2 No. 60950-1 (c-UL)	Scanning Speed
Environmental Standard	ENERGY STAR certified	Modem Speed
Printer Specification	ons	Transmission Speed
CPU	SP C252DN: 350MHz SP C252SF: 400MHz	Memory Backup SAF Memory
Fonts	PCL 5c, PCL 6, PostScript 3 emulation PCL/PS: 80 fonts	One-Touch/Speed Dials
RAM Memory	SP C252DN: 128 MB RAM standard/maximum SP C252SF: 256 MB RAM standard/maximum	Facsimile Features
Interfaces	USB 2.0, 10/100Base-TX Ethernet, USB Host Interface for PictBridge", IEEE 802.11 b/g/n (Hardwired and wireless Ethernet network	
	connections cannot be active simultaneously)	
Network Protocols Printer Features	TCP/IP (IPv4, IPv6), IPP, Bonjour Locked Print, Collate, Layout (N-up), Duplex, Front Cover Sheet, Economy Color, Watermark, User ID, User Code, Rotate Print, Ricoh Smart Device Print&Scan app (device must be set to	
	[PCL 6 mode] > [Universal]), Dithering, Do Not Print Blank Pages, Reduce/Enlarge Print, Toner Saving	Hardware Acces Paper Feed Unit
Conjer Specificatio	ons (SP C252SF Only)	Type TK1010
First Copy Speed	20 seconds or less for both B&W and Full-Color	Capacity Acceptable Paper Size
Multiple Document/ Single Copy Speed	20 cpm B&W/12 cpm Full-Color	Acceptable Paper Weig Dimensions (WxDxH) Weight
Copy Resolution	1200 x 1200 dpi (scanning) 600 x 600 dpi (printing)	Consumables
Original Type Original Size	Sheet/Book/3D Objects Up to 8.5" x 11" (Platen)	Print Cartridge Black SP C252HA
Quantity Indicator	Up to 8.5" x 14" (ADF) 1 – 99	Print Cartridge Cyan SP C252HA
Zoom	25% – 400% in 1% increments Reduction Ratios: 50%, 65%, 78%, 93% Enlargement Ratios: 129%, 155%, 200%, 400%	Print Cartridge Magen SP C252HA Print Cartridge Yellow SP C252HA
Copier Features	Image Density Adjustment (manual only: 5 levels)	Waste Toner Bottle Type 220
	Copy Mode (Text/Photo/Mixed) Color Balance Adjustment Combine Copy (2-in-1, 4-in-1 via ADF only)	*Declared yield values in ac
	Duplex Copy ID Card Copy (2 in 1)	based on types of images p The Ricoh SP C252DN and
	Memory Copy Photo Mode	print cartridges yielding 1,0
··· ·	Electronic Sorting (collation, ADF only)	For maximum performance and supplies.
	ions (SP C252SF only)	
Scan Modes Compression	Full-Color, B&W, Grayscale B&W: TIFF (MH/MR/MMR), JPEG, PDF	Specifications subject to ch

Compression	B&W: TIFF (MH/MR/MMR), JPEG, PDF
	Color/Grayscale: JPEG, PDF
File Format	Single/Multi-Page TIFF, Single/Multi-Page PDF,
	Single Page JPEG
Scan Resolution	Up to 1200 x 1200 dpi (optical)
	Up to 19200 x 19200 dpi (interpolated)
Scan Speed	B&W: Less than 5 seconds per page
	Grayscale: Less than 5 seconds per page
	Full-Color: Less than 10 seconds per page
Scan Interface	USB 2.0, 10/100Base-TX Ethernet, IEEE
	802.11 b/g/n
Utilities & Drivers	TWAIN Driver, Presto! PageManager version
	9.33
Scanning Features	Image Density (adjustable with 5 steps),
-	TWAIN/WIA; Scan-to-Email/Folder/FTP/USB

nile Specifications (SP C252SF only) PSTN, PBX Super G3 Standard Mode: 200 x 100 dpi bility on Fine Mode: 200 x 200 dpi MH/MR/MMR/JBIG sion Method Less than 5 seconds per page (B&W) Less than 10 seconds per page (Full-Color) 33.6 Kbps with automatic fallback Speed Speed 3 seconds per page (base on ITU-T Test sion Speed Chart #1 in Standard mode) Backup No limit 2MB (Approx, 100 pages based on ITU-T Test nory Chart #1 in Standard mode) 20 locations/200 locations ch/Speed Dials Features Auto Redial, Auto Answer (3 – 5 rings), Auto/Manual/Substitute/Authorized Reception, Answering Machine Interface (FAX/TAD), Error Correction Mode, User Codes, Memory/Immediate Transmission, Resolution Adjustment, Serial Broadcasting (100 locations), Smoothing, Night Timer, Internet Fax, LAN Fax, PC Fax (Windows only), Paperless Fax (Reception File Setting, Print Received File, Print Forward File, Notify Forward Status) vare Accessories ed Unit Part # 406019 (1010 500 sheets Letter (8.5" x 11"), A4 (8.3" x 11.7") 16 – 28 lb. Bond (60 – 105 g/m²) 16" x 18" x 5" (400 x 450 x 127mm) ole Paper Size ole Paper Weight ons (WxDxH) 13.2 lb. (6 kg) imables Part # 407653 rtridge Black 6,500 pages* rtridge Cyan 6.000 pages* Part # 407654 HA rtridge Magenta 6,000 pages* Part # 407655

vield values in accordance with ISO/IEC 19798. Actual yields may vary types of images printed and other factors

6,000 pages*

Part # 407656

25.000 pages Part # 406043

SP C252DN and SP C252SF ship with a set of four starter All-In-One idges yielding 1,000 pages each. All other consumables ship at full yield

um performance and yield, we recommend using genuine Ricoh parts

ons subject to change without notice.

Warranty

The Ricoh SP C252DN/SP C252SF is under warranty against defects for a period of one year from the date of purchase. Consumables are under warranty for a period of 90 days from the date of purchase or until depleted, whichever comes first. Please refer to warranty documents shipped with the product for more details.



www.ricoh-usa.com

Ricoh Americas Corporation, 70 Valley Stream Parkway, Malvern, PA 19355, 1-800-63-RICOH Ricoh* and the Ricoh Logo are registered trademarks of Ricoh Company, Ltd. All other trademarks are the property of their respective owners. ©2014 Ricoh Americas Corporation. All rights reserved. The content of this document, and the appearance, features and specifications of Ricoh products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or waranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will avy depending upon use of the products and and the conditions and factors affecting performance. The only warranties for Ricoh products and services are as set forth in the express warranty statements accompanying them.

